



Screwless Connectors Block Connectors

930-02/ 1

Terminal Block with 2 Release Keys, 1 pole, Voltage Rating: 450 V,
Current Rating: 24 A, Cross-Section: 2.5 mm²



Order Info

Reference Number (ref. no.)	112401
Applications	Lighting, Electrical Appliances
PU	2,500
EAN	4028012104253

Type

Type	Terminal Block with 2 Release Keys
Number of poles	1 pole
Clamping Units per Pole	2
Colour	white
Cross-Section	2.5 mm ²
Connection Type	screwless

Technical Data

Voltage Rating	450 V
Current Rating	24 A
Insulating Material	PA 6.6
Contact Material	Brass
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Stripping Length	8-9 mm
Internal Core Cross-Section max.	2.5 mm ²
External Core Cross-Section min.	0.5 mm ²
External Core Cross-Section max.	2.5 mm ²
Internal Core Cross-Section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Solid Internal	yes
Approbation EN60998	930_935_937_EN60998_20071001_VDE_40022275_web.pdf
Approbation UL	930_935_19880415_19941222_UL_E63492_1-06_Description_web.
Approbation CSA	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765

Accessories

ZEL 110

196420
