

## MLP1 ESD Suppressor PolySurg™ 0402ESDA-MLP1



### Description

The Cooper Bussmann PolySurg™ 0402ESDA-MLP1 ESD Suppressors protect valuable high-speed data circuits from ESD damage without distorting data signals as a result of its ultra-low (0.05pF typical) capacitance.

### Features

- Halogen free
- RoHS compliant for global applications
- Lead free
- Ultra-low capacitance (0.05pF typ.) ideal for high speed data applications
- Provides ESD protection with fast response time (<1ns) allowing equipment to pass IEC 61000-4-2 level 4 test
- Single-line, bi-directional device for placement flexibility
- Low profile 0402/1005 design for board space savings
- Low leakage current (<0.1nA typ.) reduces power consumption
- (Sn) Tin-plated version available

### Specifications

| Characteristic                   | Value                          |
|----------------------------------|--------------------------------|
| Rated Voltage                    | 30Vdc maximum                  |
| Clamping Voltage <sup>1</sup>    | 35V typical                    |
| Trigger Voltage <sup>2</sup>     | 300V typical                   |
| Capacitance (@1MHz)              | 0.05pF typical, 0.15pF maximum |
| Attenuation Change (0-6GHz)      | -0.2dB typical                 |
| Leakage Current (@12Vdc)         | <0.1nA typical                 |
| ESD Capability                   |                                |
| • IEC61000-4-2 Direct Discharge  | 8kV typical                    |
| • IEC61000-4-2 Air Discharge     | 15kV typical                   |
| ESD Pulse Withstand <sup>3</sup> | >1000 typical                  |

<sup>1</sup> Per IEC61000-4-2, Level 4 waveform (8kV direct, 30A) measured 30ns after initiation of pulse.


<sup>2</sup> Trigger measurement made using Transmission Line Pulse (TLP) method.

<sup>3</sup> Minor shifting in characteristics may be observed over multiple ESD pulses at very rapid rate

### Applications

- Computers and peripherals
- HDTV Equipment
- DVD Players
- A/V Equipment
- Satellite radio
- Cell phones
- PDAs
- Digital still cameras
- Digital camcorders
- MP3/Multimedia players
- Set top boxes
- External storage
- DSL Modems
- High speed data ports
- USB 2.0/3.0
- IEEE 1394b
- HDMI 1.3
- DVI
- High speed ethernet
- Infiniband®

### Part Numbering System: 0402 ESDA MLP 1



### Packaging

- 10,000 suppressors on paper tape in seven inch (178mm) plastic reel per EIA Standard 481-1.

### Ordering Information

| Catalog Number | Description                                                  |
|----------------|--------------------------------------------------------------|
| 0402ESDA-MLP1  | 10,000 pieces on paper tape on 7" (178mm) reel - tin plating |

### Design Considerations






The location in the circuit for the MLP series has to be carefully determined. For better performance, the device should be placed as close to the signal input as possible and ahead of any other component. Due to the high current associated with an ESD event, it is recommended to use a "0-stub" pad design (pad directly on the signal/data line and second pad directly on common ground).

**Environmental Specifications**

| Characteristic              | Value                                                          |
|-----------------------------|----------------------------------------------------------------|
| Load Humidity               | 12Vdc per EIA/IS-772 Para. 4.4.2, +85°C, 85% RH for 1000 hours |
| Thermal Shock               | EIA/IS-722 Para. 4.6, Air-to-Air -55°C to +125°C, 5 cycles     |
| Moisture Resistance Test    | MIL-STD-202G Method 106G, 10 cycles                            |
| Mechanical Shock            | EIA/IS-722 Para. 4.9                                           |
| Vibration                   | EIA/IS-722 Para. 4.10                                          |
| Resistance to Solvent       | EIA/IS-722 Para. 4.11                                          |
| Operating Temperature Range | -55°C to +125°C                                                |
| Storage Temperature Range   | -55°C to +125°C                                                |

**Soldering Recommendations**

- Compatible with lead and lead-free solder reflow processes
- Peak reflow temperatures and durations:
  - IR Reflow = 260°C max for 10 sec. max.
  - Wave Solder = 260°C max. for 10 sec. max.
- Recommended IR Reflow Profile:

**Recommended Pad Layout - in (mm)****Dimensions - in (mm)****Tape and Reel Specifications - mm**

| Carrier Dimensions |       |       |                |                |       |      |                |                |                |       |       |
|--------------------|-------|-------|----------------|----------------|-------|------|----------------|----------------|----------------|-------|-------|
| A                  | B     | D     | E <sup>1</sup> | E <sup>2</sup> | F     | G    | P <sup>1</sup> | P <sup>2</sup> | P <sup>3</sup> | T     | W     |
| 0.75               | 1.25  | 1.50  | 1.75           | 6.25           | 3.50  | 0.75 | 4.00           | 2.00           | 4.00           | 0.43  | 8.00  |
| ±0.05              | ±0.05 | ±0.10 | ±0.10          | ±0.30          | ±0.05 | min. | ±0.10          | ±0.05          | ±0.05          | ±0.05 | ±0.20 |

10,000 pieces in paper tape on 7 inch (178mm) plastic reel per EIA Standard 481-1

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.