

DISPLAY MIPAN

	Profibus-DP	Profinet IO RT	Serial	A-D Converter
	Display			
Display type	7 segment LED			
Display colour	red			
	Data input & presentation			
Interface	Profibus-DP	Profinet IO RT	RS232, TTY, RS485 (bus compatible)	-
Transmission rate	9,6 KBit/s to 12 MBit/s	100 Mbit/s	1,2 / 2,4 / 4,8 / 9,6 KBit/s	-
Addresses Parities	0...126	device name	01...99 even, odd, no	-
Displayable characters	0...9, H, E, L, P, -, Blank	0...9, A, b, c, d, E, F, G, H, I, J, L, n, o, P, q, r, S, t, u, y, -, ., (,)	0...9, A, b, C, d, E, F, n, o, P, r, U, -, .	000...±1999
Digits character height reading distance	6 digits 13 mm 5 m	6 digits 13 mm 5 m	6 digits 13 mm 5 m	3 1/2 digits 13 mm 5 m
	Housing & mounting			
Housing	DIN panel-mount housing, metal, surface finishing			
Housing dimensions (W x H x D)	96 x 24 x 60 mm			
	Power supply			
Operating voltage	24 VDC ±20%			
Current consumption	ca. 75 mA	ca. 75 mA	120 mA	40 mA
	Environmental conditions			
Protection	front panel IP65			
Operating temperature	0...+50° C			
Storage temperature	-25...+70° C			